

FLAT ROOFS



PETRAROOF-D MW-EN13162-T5-CS(10)40-PL(5)500-WS-MU1-AFr5 (d=20mm-29mm)
 PETRAROOF-D MW-EN13162-T5-DS(70,90)-CS(10)40-PL(5)500-WS-WL(P)-MU1-AFr5 (d=30mm-150mm)
 PETRAROOF-D MW-EN13162-T5-CS(10)40-PL(5)500-WS-MU1-AFr5 (d=151mm-190mm)

PETRAROOF-D

$\lambda_D = 0,037$ [W/mK]

DIMENSIONS AND PACKAGING

FORMAT OF PLATES			PALLETS		
Length	Width	Thickness	No. of packages on a pallet	Cover surface of plates on a pallet	Volume of plates on a pallet
[mm]	[mm]	[mm]	[pcs.]	[m ²]	[m ³]
2000	1200	20	50	120,00	2,400
		30	40	96,00	2,880
		40	30	72,00	2,880
		50	24	57,60	2,880
		60	20	48,00	2,880
		70	17	40,80	2,856
		80	15	36,00	2,880
		90	13	31,20	2,808
		100	12	28,80	2,880
		110	10	24,00	2,640
		120	10	24,00	2,880
		150	8	19,20	2,880
		160	7	16,80	2,688
		170	7	16,80	2,856
		180	6	14,40	2,592
		190	6	14,40	2,736

EFFECTIVE AND ECONOMICAL

Using mineral stone wool as thermal, sound or fire insulation contributes to significant savings and environmental

protection by reducing consumption of energy and carbon dioxide emission to the atmosphere.